

Product Name :
Tapped Density Tester

Product Code :
TEST5178RFQLAB-0008



Description :

Tapped Density Tester

Technical Specification :

Tapped Density Tester: Compact tester that combines two USP / Ph.Eur. Methods in one instrument with small footprint requirements. Print test protocols and connect your external analytical balance for automated transfer of weight readings.

Full Pharmacopeia compliance and password protection to prevent unauthorized access. Combines two test methods with different stroke heights in one compact instrument.

Full compliance with USP Method 1/2 and Ph.Eur. 2.9.24 Method 1/2. Printed test protocols that include tapped density calculations, Compressibility Index, and Hausner Ratio. Password protection to prevent unauthorized access and menu-guided qualification procedure with printed report.

Easy and fast operation with quick-lock cylinders and Single Button operation. Different cylinder sizes and volumes possible.

Number of test stations : 2 glass cylinders

Stroke height Strokes / min : 14 mm \pm 2 mm, 300 strokes/min. \pm 15 according to USP method 1

Keypad : Membrane function keypad (touch pad)

Display : 2 illuminated LED displays (or one)

Preselection of test run time: In time: 1 sec. to 9 hrs., 59 min., 59 sec.

Number of strokes : 1 to 9999 .



Testing lab instruments India